## IN THE CLAIMS

Claims 1-6 (Canceled)

- 7. (New) A magnetic recording medium made by forming at least a magnetic layer and an overcoat on a non-magnetic substrate, said overcoat having a surface on which a liquid lubricant of a perfluoropolyether structure is coated, wherein the surface of said overcoat has less that 0.8 nm average roughness Ra, said overcoat is a layer of diamond-like-carbon with less than 5 nm thickness, and said lubricant coat on said overcoat contains said perfluoropolyether structure having cyclic phosphazene at the end of said perfluoropolyether structure.
- 9. (New) A magnetic recording medium according to claim 7, wherein said lubricant coat contains more than 30% of a

lubricant component having a perfluoropolyether structure containing  $-(OC_2F_4)_p-$ ,  $-(OCF_2)_q-$ , and a structure represented by:

$$-(O-C_6H_3(-CF_3))_x$$
 .....(A)  
(where p=5-36, q=4-30, x=1-5)

10. (New) The magnetic recording medium according to claim 7, wherein a principal chain of said lubricant component has a perfluoropolyether structure containing  $-(OC_2F_4)_p$ -,  $-(OCF_2)_q$ -, am end group of said lubricant component has a structure represented by:

$$-(O-C_6H_3(-CF_3))_x$$
 .....(A)

(where p=5-36, q=4-30, x=1-5)

and said principal chain has an average molecular weight of 1500-2500.

11. (New) A magnetic recording medium made by forming at least a magnetic layer and an overcoat on a non-magnetic substrate of a disk, said overcoat having a surface on which a liquid lubricant of a perfluoropolyether structure is coated, wherein the surface of said overcoat has less than 0.8 nm average roughness Ra, said overcoat is a layer of diamond-like-carbon with a thickness in a range of 1.5 - 4.5 nm, and

said lubricant coat on said carbon overcoat contains said perfluoropolyether structure having cyclic phosphazene at the end of said perfluoropolyether structure.

- 12. (New) A magnetic recording medium according to claim 11, wherein said perfluoropolyether structure contains  $-(OC_2F_4)_p-$ ,  $-(OCF_2)_q-$ , and a structure represented by:  $-(O-C_6H_3(-CF_3))_x$  .....(A) (where p=5-36, q=4-30, x=1-5)
- 13. (New) A magnetic recording medium according to claim 11, wherein said lubricant coat contains more than 30% of a lubricant component having a perfluoropolyether structure containing  $-(OC_2F_4)_p-$ ,  $-(OCF_2)_q-$ , and a structure represented by:

$$-(O-C_6H_3(-CF_3))_x$$
 .....(A)  
(where p=5-36, q=4-30, x=1-5)

14. (New) The magnetic recording medium according to claim 11, wherein a principal chain of said lubricant component has a perfluoropolyether structure containing  $-(OC_2F_4)_p$ -,  $-(OCF_2)_q$ -, an end group of said lubricant component has a structure represented by:

. Serial No. 10/613,091

NIT-277-02

$$-(O-C_6H_3(-CF_3))_x$$
 .....(A)

(where p=5-36, q=4-30, x=1-5)

and said principal chain has an average molecular weight of 1500-2500.